

## TECHNICAL DATA SHEET

Version: 2025.05.EN

### Ritec AF film

#### PRODUCT DESCRIPTION

Ritec AF is a transparent polyester-based film (BOPET) with an antifog coating on one side. The other side of the film is corona-treated. Thanks to the applied antifog layer, the film ensures good visibility of the packaged product even with increased humidity inside the packaging. The film also has a high gloss and good transparency. Thanks to the above properties and high mechanical strength, the film can be successfully used as a packaging material. The film is approved for food and pharmaceutical packaging.

#### SPECIFICATIONS

Properties	Um	Typical value			Comments
Thickness	µm	50	75	100	(+/-5%)
Roll width max.	mm	2000			(+/-2mm)
Yield	m <sup>2</sup> /kg	14,3	9,5	7,1	(+/-5%)
Unit weight	g/m <sup>2</sup>	69,95	105,26	140,85	(+/-5%)
Surface tension min.	dyn/cm	54	54	54	ASTM D-2578
Tensile strength - machine (MD) - transverse (TD)	kg/cm <sup>2</sup>	1900 2000	1700 1900	1600 1700	ASTM D-882
Elongation at break - machine (MD) - transverse (TD)	%	170 150	190 170	200 180	ASTM D-882
Thermal shrinkage - machine (MD) - transverse (TD)	%	1,6 0,2	1,2 0,2	1,2 0,2	ASTM D-1204 (150°C @ 30min)
Haze	%	4,2	3,8	4,5	ASTM D-1003
Coefficient of friction - static - dynamic	-	0,38 0,30	0,38 0,30	0,38 0,30	ASTM D-1894
Standard roll length	m	3000	2000	1500	(+/-15%)

#### INTENDED USE

Type of application: packaging production.

#### STORAGE CONDITIONS AND SHELF LIFE

The products should be stored away from sources of high and low temperatures, humidity and direct sunlight. The recommended storage temperature is 5°C - 30°C with relative humidity of 20% - 70%. Product shelf life is 6 months from production date printed on the label.

#### ADDITIONAL INFORMATION

The data presented are based on the current state of our knowledge and are intended for information purposes only. The specified parameters represent typical values and do not represent limit values. Given the number of factors beyond our control, we cannot guarantee the properties or suitability of the products for each individual case of application. For these reasons, no legal claims may be derived from this technical specification sheet. We reserve the right to update the technical specifications at any time without any obligation to inform you. The product is not classified as hazardous, we recommend reading the declaration of conformity before use. Dispose of in accordance with local and national regulations.